



# HEBEL CORRIDOR WALLS

FOR MAXIMUM FLOOR SPACE WITH CONCEALED SERVICES ON ONE SIDE

Hebel1148 - 1149




VERTICAL CROSS SECTION DETAIL A-A



DETAIL PLAN VIEW

PLAN VIEW



ISOMETRIC VIEW

NTS

CORRIDOR WALL

CODE	APPLICATION	WALL THICKNESS	WALL HEIGHT 'H'	FRL <sup>®</sup>	R <sub>s</sub>	SYSTEM COMPONENT VARIATIONS			
						LINING A	MIN. GAP	INSULATION <sup>(A)</sup>	LINING B
Hebel1148	DRY TO DRY	180mm	UP TO 3.3m HIGH	-90/90 FOR WALL HEIGHTS UP TO 3.3m	58	13mm GYPROCK CD	15mm	50mm BRADFORD ACOUSTIGARD 11	13mm GYPROCK CD
Hebel1149	DRY TO WET	180mm	UP TO 3.3m HIGH	-90/90 FOR WALL HEIGHTS UP TO 3.3m	59	13mm GYPROCK CD	15mm	50mm BRADFORD ACOUSTIGARD 11	13mm AQUACHEK

REFER TO DESIGN AND INSTALLATION GUIDES FOR HIGH RISE INTERFERENCE AND SERVICE WALLS (HEB 1364) FOR MORE CONSTRUCTION AND PRODUCT INFORMATION. 13mm AQUACHEK CAN BE REPLACED BY 9mm FIBRE CEMENT SHEETING AND ACHIEVE THE SAME FRL AND ACOUSTICS. FOR WALLS > 3.3m AND ≤ 4.65m, CAGED TONGUE & GROOVE POWERPANEL CAN BE USED AND WILL ACHIEVE A FRL OF +120/120. REFER TO DESIGN AND INSTALLATION GUIDES FOR SHAFT AND SCISSOR STAIR WALLS (HELT 092) FOR MORE DETAILED INFORMATION.



CSR BUILDING PRODUCTS LTD  
HEAD OFFICE: 7 TULLOCH ROAD NORTH, SYDNEY NSW 2113  
A.B.N. 55 008 631 396 P.O. BOX 299 448  
WWW.HEBELBUILD.COM.AU



CSR Building Products Limited  
A.B.N. 55 008 631 396  
1120 Pittwater Road, Pittwater NSW 1505  
Phone: 02 9392 2288 Fax: 02 9392 2289

SYSTEM CODE	TITLE	HEBEL CORRIDOR WALLS	REVISION	DATE	BY	CHK	APP
Hebel1148 - 1149	SCALE	1:5 @ A3	1 of 1	15.04.20			