



HEBEL CORRIDOR WALLS FOR MAXIMUM FLOOR SPACE WITH CONCEALED SERVICES ON ONE SIDE

Hebel1150 - 1151




VERTICAL CROSS SECTION DETAIL A-A



DETAIL PLAN VIEW

ISOMETRIC VIEW



CODE	APPLICATION	WALL THICKNESS	WALL HEIGHT	FRL [®]	SYSTEM COMPONENT VARIATIONS		
					LINING A	MIN. GAP	LINING B
Hebel1150	DRY TO DRY	144mm	UP TO 3.3m HIGH	52	13mm GYPROCK CD	43mm	50mm BRADFORD GYPROCK CD
Hebel1151	DRY TO WET	144mm	UP TO 3.3m HIGH	53	HEBEL SIDE-13mm GYPROCK CD	43mm	50mm BRADFORD AOUACHEK

REFER TO DESIGN AND INSTALLATION GUIDES FOR HIGH RISE INTERPENANCY AND SERVICE WALLS (HEB 1354) FOR MORE CONSTRUCTION AND PRODUCT INFORMATION. 13mm AOUACHEK CAN BE REPLACED BY 9mm FIBRE CEMENT SHEETING AND ACHIEVE THE SAME FRL AND ACOUSTICS. FOR WALLS > 3.3m AND ≤ 4.65m, CAGED TONGUE & GROOVE POWERPANEL CAN BE USED AND WILL ACHIEVE A FRL OF +120/120. REFER TO DESIGN AND INSTALLATION GUIDES FOR SHAFT AND SCISSOR STAIR WALLS (HELT 032) FOR MORE DETAILED INFORMATION.

CSR BUILDING PRODUCTS LTD
 Head Office: 7111-7131, 20 DUNDAS STREET WEST, TORONTO, ONTARIO M5G 1S7
 A.B.N. 55 008 631 396 Fax: 1 800 389 448
 www.hebelproducts.com.au

hebel The Builder's Way to Build

PRODUCT CODE	Hebel1150 - 1151	TITLE	HEBEL CORRIDOR WALLS
DESIGN DATE	---	SCALE	1:5 @ A3
REVISION	---	DRAWN	ET
		CHECK	CW
		DATE	15.04.20
		PROJECT	C